



CONCRETE MIXERS

CONCRETE & MASONRY EQUIPMENT

Toro®'s broad line of concrete mixers offers a model for every application, in both gas and diesel. The towable mixers feature a convenient hand wheel to provide greater operator control and the ability to lock the drum in any position for easy mixing and storing. A reinforced front post adds strength to the wider axle design for more comfortable towing, Toro concrete mixers offer standard features that equate to deluxe performance.

FEATURES

EASY OPERATION

- Sturdy hand wheel provides a convenient way to control dumping
- Cowl-mounted engine shutoff switch is easily accessible for operator safety
- The engine cowl features a cut out to allow engine access without leaving the cowl open
- Easy-to-clean polyethylene drum options available on select models
- Positive gear and dog drum lock secures drum in one of 90+ positions to accommodate mixing and storing needs
- Easily accessible grease fittings make routine maintenance fast and simple

HIGH QUALITY CONSTRUCTION

- Oversized steel paddles mean fast, complete mixing and long lasting durability
- Heavy-duty, one-piece cast iron ring gear delivers smooth operation and longer life
- High quality greasable tapered roller bearings on a large diameter shaft make drum rotation and emptying quick and easy
- Downward pitched, heavy-duty tow pole delivers superior strength and provides high clearance over ground and curbs
- Reinforced front post provides maximum strength in high stress areas
- Full-length rust-proof brass cowl hinge provides superior stability and strength to extend cowl life
- Spacious reinforced steel cowl offers opening for easier access to engine while delivering more air volume for cooler engine operation and engine life



CM-1258Y-SD Mortar Mixer



Toro mixers are built based on the proven quality and performance of Stone Construction Equipment's original design.

CONCRETE MIXER LINEUP

SPECIFICATIONS

	CM-658H (68004)	CM-958H (68006 & 68009) CM-958H-SED (68007 & 68008)	CM-1258Y (68011)
Batch Capacity* - Bags	1/2 - 1 bag	1 - 1.5 bags	3 - 4 bags
Batch Capacity* - Volume	6 cu. ft.	9 cu. ft.	12 cu. ft.
Total Drum Volume	9.0 cu. ft.	15.1 cu. ft.	19.8 cu. ft.
Engine	Honda® GX240	Honda GX240	Yanmar® L100V Diesel
Drum Options	Steel Side Dump	Steel or Plastic Side Dump or End Dump	Steel Side Dump
Drive	Belt Drive	Belt Drive	Chain Drive
Wheels, Bearings & Axle	4.8 x 12 (20" diameter) high speed tires, tapered roller bearings, 46" wide axle	B78 x 13 (25" diameter) high speed tires, tapered roller bearings, 56" Axle/Cantilever Springs	B78 x 13 (25" diameter) high speed tires, tapered roller bearings, 56" Axle/Cantilever Springs
Dimensions (L x W x H)	84" x 56" x 65"	Side Dump: 84" x 56" x 65" End Dump: 85" x 85" x 71"	95" x 56" x 70"
Weight	690 lbs.	800 - 875 lbs.	897 lbs.

Accessories** Side dump mixers: Stamped, forged, and pintle hitch options
End dump mixers: Welded tow pole with 1" pin hitch, Trailer light kit

*Batch capacity varies based on 94 lb bags of Portland Cement premix.

** Towable mixers for Canada are sold with trailer lights installed as standard - limited models.



Tow Pole Options

Select from three different tow pole options, pintle, stamped, or forged, for easy towing to maximize your job site efficiency.