



ULTRAMIX™ MORTAR MIXERS

CONCRETE & MASONRY EQUIPMENT

THE TORO® ULTRAMIX MORTAR MIXER is the ultimate in mixing performance. Together, the symmetrical drum design and patented paddle configuration provide more paddle and drum contact with the mortar for a faster, more blended mix. A smooth mixture with more entrained air extends board life and is easy to work with to keep masons extremely productive. In addition to elite performance, the UltraMix mortar mixer has an extremely durable design with heavy-duty construction, reinforced paddle rubber and high strength steel for extended mixer life. The 6 and 8-cubic foot mixers come in either steel or polyethylene drum and offer the best speed and mixing consistency on the market - perfect for busy concrete and masonry contractors.

FEATURES

ULTIMATE MIXING PERFORMANCE

- Patented paddle design moves mix back and forth horizontally as well as in the circular motion, to create a smoother mixture for greater efficiency.
- Symmetrical drum design eliminates dead zone and increases mortar to drum contact for a thorough, smooth mix.

SUPERIOR DESIGN

- The engine cab features an open design to allow the operator easy access to start the engine without the need to lift the hood. The cowl venting design provides better air flow to cool the engine during use.
- Drum sealing system design has four long-life seals at each end of the paddle shaft to eliminate leakage. Includes a lifetime warranty.

HEAVY-DUTY CONSTRUCTION

- High strength steel offers enhanced durability to extend mixer life.
- Strengthened paddle rubber with two layers of fabric woven into rubber is strong, minimizes tearing and extends paddle life to reduce replacement maintenance.
- Solid steel dump handle provides maximum strength when pouring mortar mixture.
- Raised tow pole hole offers greater leverage to make for easier lifting, moving and trailering mixer.

LIFETIME WARRANTY

If the bearing(s) or seal(s) on your mixer fail, they will be replaced under warranty, at no cost for parts or labor. See the warranty statement for full details.



PATENTED PADDLE DESIGN

Optimized paddle configuration is extremely efficient and increases paddle to mortar contact for smoother mix and extremely efficient mixing.



ULTRAMIX MMX-858K-P



ULTRAMIX MMX-858H-S

ULTRAMIX™ MORTAR MIXERS



TELESCOPING AXLE

Axle can extend to 46" for towing and retracts to fit through gates and doorways for greater maneuverability in tight spaces.



EASY-TO-ACCESS

Engine cowl features a heavy duty hinge and lifts up for easy access to components



BAG SPLITTER

Optimized bag splitter design easily slices mortar bags to increase productivity when mixing mortar.

SPECIFICATIONS

	MMX-650E-S (60212)	MMX-655H-S MMX-658H-S (60213, 60216)	MMX-658K-P (60217)	MMX-850E-S (60218, 60219)	MMX-858H-S (60220)	MMX-858K-P (60221)
Batch Capacity* Volume	6 cu. ft. (.17 m ³)	6 cu. ft. (.17 m ³)	6 cu. ft. (.17 m ³)	8 cu. ft. (.23 m ³)	8 cu. ft. (.23 m ³)	8 cu. ft. (.23 m ³)
Total Drum Volume*	7.1 cu. ft. (.20 m ³)	7.1 cu. ft. (.20 m ³)	6.7 cu. ft. (.19 m ³)	9.0 cu. ft. (.25 m ³)	9.0 cu. ft. (.25 m ³)	8.6 cu. ft. (.25 m ³)
Engine	1.5 HP Electric 115V-230V	Honda® GX 160 or Honda GX240	Kohler® 9.5HP (gross)	1.5 HP or 2HP Electric 115V-230V	Honda GX240	Kohler 9.5HP (gross)
Drum Options	0.12" (3 mm) Thick, High Strength Steel		0.5" Polyethylene	0.12" (3 mm) Thick, High Strength Steel		0.5" Polyethylene
Drive & Clutch	Belt drive, front post hand clutch			Belt drive, front post hand clutch		
Wheels, Bearings & Axle	4.80 x 12 (20" (51 cm) diameter) High-Speed tires, Tapered Roller Bearings, 46" (117 cm) Axle - Extendible, Safety Chain			B78 x 13 (25" (64 cm) diameter) High-Speed tires, Tapered Roller Bearings, 46" (117 cm) Axle - Extendible, Safety Chain		
Dimensions (LxWxH)	59"x34"x54" (150 x 86 x 137 cm)	59"x34"x54" (150 x 86 x 137 cm)	59" x 34" x 56" (150 x 86 x 142 cm)	66"x34"x54" (168 x 86 x 137 cm)	66"x34"x54" (168 x 86 x 137 cm)	66" x 34" x 56" (168 x 86 x 142 cm)
Weight	634 lbs (287 kg)	599 lbs, 621 lbs (271 kg, 282 kg)	552 lbs (250 kg)	649 lbs, 658 lbs (294 kg, 298 kg)	636 lbs (288 kg)	560 lbs (254 kg)
Accessories**	← Choice of tow pole hitch options: forged, pintle or stamped & trailer light kit →					

*Batch capacity varies based on ratio of material used.

** Towable mixers for Canada are sold with trailer lights installed as standard.

